

# INSTALLATION AND ASSEMBLY INSTRUCTIONS



## STRAUBELSTONE STEELMAN & EXECUTIVE GAS BARBECUE CART SIDE PANELS

These StraubelStone Steelman Gas Barbecue Cart Side Panels have been designed as retro-fit accessories, for the StraubelStone Steelman Gas Barbecue Cart. Other accessory items are available from your retailer, or may be purchased by contacting the StraubelStone Customer Service Center.

## GENERAL INFORMATION

These instructions are intended as a general guide and do not supersede national or local codes in any way. Authorities having jurisdiction should be consulted before installation.

## !!! IMPORTANT !!!

Read these instructions carefully before installation. These instructions should be left with the homeowner for future reference.



GAS-FIRED OUTDOOR COOKING  
APPLIANCE IN ACCORDANCE WITH THE  
AMERICAN NATIONAL STANDARDS  
INSTITUTE (ANSI) STANDARD FOR  
OUTDOOR COOKING GAS APPLIANCES  
Z21.58-1995 83EK

## SHIPPING AND PACKING LIST

### SHIPPING CARTON CONTAINS:

- 2- StraubelStone Steelman Gas Barbecue Cart Side Panels
- 8- 1/4 - 20 x 1/2" Stainless Steel Button Head Screws
- 8- 1/4" Stainless Steel Washers

## SET UP AND ASSEMBLY

The following assembly may require two ( 2 ) people.

For reference purposes, it is recommended that you use the StraubelStone Steelman Gas Barbecue Cart manual.

- 1- **TURN OFF THE GAS SUPPLY!** NEVER attempt any assembly operation while the appliance is in operation or is HOT.
- 2- Open the shipping container.
- 3- Remove all contents from the shipping container.
- 4- Check the contents of the shipping container against the shipping and packing list. Report any missing or damaged parts to your retailer.
- 5- Remove the Liquid Propane Tank Hook.
- 6- Disconnect and remove the Liquid Propane Tank. ( SEE STRAUBELSTONE STEELMAN GAS BARBECUE CART MANUAL )
- 7- Remove the barbecue hood. ( SEE HOOD ASSEMBLY IN STRAUBELSTONE STEELMAN GAS BARBECUE CART MANUAL )
- 8- Remove cooking grates.
- 9- Remove burner plate.
- 10- Carefully tilt the barbecue cart towards the rear, until it rests on its back side.
- 11- Place one ( 1 ) side panel ( panels are identical ) aligning the three ( 3 ) hole pattern edge, into the bottom edge of the cart chassis top. While, slightly, tilting the side panel away from the cart frame, replace the LP Tank Hook into the center hole.
- 12- Press side panel into place.
- 13- Using a 5/32" male hex driver, attach the side panel to the cart chassis, and the LP tank mount, using four ( 4 ) Button Head Screws and four ( 4 ) washers, but do not tighten.

## SET UP AND ASSEMBLY continued

- 14- Check the assembly for a flush and level fit, and then tighten all four ( 4 ) screws evenly. Do not over tighten. ( SEE FIGURE 1 )
- 15- Place the other side panel, on the opposite side of the cart, aligning the three ( 3 ) hole pattern edge, into the bottom edge of the cart chassis top.
- 16- Press side panel into place.
- 17- Using a 5/32" male hex driver, attach the side panel to the cart chassis, using four ( 4 ) Button Head Screws and four ( 4 ) washers, but do not tighten.
- 18- Check the assembly for a flush and level fit, and then tighten all four ( 4 ) screws evenly. Do not over tighten. ( SEE FIGURE 1 )
- 19- Carefully lift the barbecue cart towards the front, until it rests on the wheels and casters.
- 20- Replace burner plate.
- 21- Replace cooking grates.
- 22- Replace the barbecue hood. ( SEE HOOD ASSEMBLY IN STRAUBELSTONE STEELMAN GAS BARBECUE CART MANUAL )
- 23- Replace and reconnect the Liquid Propane Tank. ( SEE STRAUBELSTONE STEELMAN GAS BARBECUE CART MANUAL )
- 24- Reconnect the Liquid Propane Tank Hook to the tank.



**FIGURE 1**

### **STRAUBELSTONE™**

16781 Noyes Ave.  
Irvine, CA 92606

(800) 640-7687  
(949) 296-0121  
(949) 296-0127 fax

e-mail – [support@straubelstone.com](mailto:support@straubelstone.com)